

# MOULDED PANEL MIDDLEWEIGHT CORE – INTERNAL DOOR

## SPECIFICATIONS

### Construction

Moulded wood fibre face with softwood stiles and rails.  
Middleweight cellular core with chipboard inner stiles.

### Door Codes

Arlington 6 panel smooth (enhanced bead detail)	ARLSL
Atherton 4 panel smooth	ATHSL
Bostonian 6 panel woodgrain	BTNSL
Cambridge 2 panel smooth	CAMBSL
Camden 2 panel woodgrain	CMNSL
Oakfield 4 panel woodgrain	OFDSL
Rockport® 5 panel smooth	ROCKSL
Newark woodgrain	NEWASL
Cube smooth	CUBESL
Linea smooth	LINESL
Newbridge smooth	NEWBSL

### Moisture Content

10% (+/-2%) in accordance with BS:EN942.

### Facings

3.0mm die-formed moulded wood fibre skin.

### Components

Stiles:	Softwood min 28mm (nominal width)
Rails:	Softwood min 28mm (nominal width)
Core:	Cellular with 55mm chipboard strips to stiles
Lockblock:	N/A
Lipping:	N/A

### Lock Area

Locks and handles may be fitted centrally in height either side of the door.

### Finish

Supplied white primed for paint finish on site. Woodgrain doors can be supplied fully finished in white semi gloss paint as an optional extra (+P) or undercoated (W).

### Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge.  
The top of the door should not be trimmed due to the manufacturing identifications.

### Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

Re-decorate the door as necessary always following the paint manufacturer's instructions.

