

# No. 08 GRANGE

## Sliding Barn Internal Doors

A sliding barn door that's a firm favourite.



### On-trend living

A sliding door has always been at home in country-style houses. Yet it's been utilised more and more in contemporary homes to create a striking design feature.

### Upscale your home

As well as its space-saving functionality, this door is easy to install and helps to create a distinctive upmarket look that will stand the test of time.

### Style and substance

An easy glide mechanism for a quieter and smoother closing action, plus a trackless design to keep flooring uninterrupted and hazard-free.

### Get the look

Whether you opt for wonderfully grained Mindi doors, grand oak veneers or a simple primed design the Grange doors are sure to attract attention.

### Find yours

Available in different styles and with multiple track options, you can customise this door to suit your needs.

### TRACK OPTIONS



### Features & benefits:

- Statement style
- Space saving solution
- Smooth, glide operation
- Uninterrupted flooring
- 5-year guarantee

# DOOR DESIGNS



Framed,  
Ledged &  
Braced (FLB)

Framed,  
Ledged &  
Braced (FLB)  
Glazed

Primed  
Cottage

Primed  
Cottage  
Glazed

Primed  
Shaker  
1 Panel

Shaker  
4 Panel

Cottage

Door sizes:

Width (mm)	Height (mm)	Depth (mm)
862	2073	35

Track length - 2m

<b>Material specification</b>	Oak - White Oak Veneer, Solid Particle Board Core Mindi - Mindi Veneer, Solid Particle Board Core Primed - Primed MDF Facing, Solid Particle Board Core
<b>Finish</b>	Oak & Mindi - Unfinished Primed - White primed
<b>Glass specification</b>	4mm Clear Toughened Glass
<b>Hardware details</b>	4 designs - Industrial (black) / Urban - black / Provincial (silver) / Elegant (silver) Black - powder coated steel / Silver - stainless steel
<b>Decoration requirements</b>	It is essential that the door is completely finished on the two faces and all FOUR edges plus any cut-outs for locks, handles and hinges etc. Prior to finishing or sealing, lightly sand any handling marks. Usually 3 top coats are satisfactory but we strongly recommend you that you treat this door in accordance with the paint, stain or varnish manufacturer's instructions. A light sanding between coats will provide the best finish. Adequate drying time must be allowed between each coat. Failure to seal the doors accordingly will invalidate any claims.
<b>Storage</b>	Doors must be stored flat in cool, dry conditions avoiding direct contact with sunlight before the door has been finished.
<b>Trimming allowance</b>	Door should not be trimmed as they are part of the sliding system.
<b>Guarantees</b>	5 Year Manufacturing, 1 Year Hardware
<b>Sustainability</b>	FSC Mix 70%
<b>Additional information</b>	Wall should be suitable for taking the weight of the door - minimum 40kg Recommended maximum opening size: (without architrave) - opening to suit 1981mm (h) x 838mm (w) (with architrave) - opening to suit 1981mm (h) x 762mm (w)



**CURATED**  
by **JELD-WEN**