

# MOULDED PANEL

## 2 LIGHT GLAZED STANDARD CORE

### – INTERNAL DOOR

#### SPECIFICATIONS

##### Construction

Moulded wood fibre face with softwood stiles and rails.  
Tubular chipboard inner stiles. Glazed with 4mm toughened glass.

##### Door Codes

WOODGRAIN:	Geometric	APOFD+GEP
	Marginal Bar	APOFD+MB
	Clear	APOFD+GCF
	Etch	APOFD+ET

ARLINGTON SMOOTH:	Geometric	APARL+GEP
	Marginal Bar	APARL+MB
	Clear	APARL+GCF
	Etch	APARL+ET

ATHERTON SMOOTH:	Geometric	APATH+GEP
	Marginal Bar	APATH+MB
	Clear	APATH+GCF
	Etch	APATH+ET

##### Moisture Content

10% (+/-2%) in accordance with BS:EN942.

##### Facings

3.0mm die-formed moulded wood fibre skin.

##### Components

Stiles:	Softwood min 28mm (nominal)
Rails:	Softwood min 28mm (nominal)
Glazing Framing:	Polystyrene
Glazing Cassette:	PVC
Core:	Cellular with 55mm chipboard strips to stiles
Lockblock:	N/A
Lipping:	N/A

##### Lock Area

Locks and handles may be fitted centrally in height either side of the door.

##### Finish

Supplied white primed for paint finish on site.

##### Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge. The top of the door should not be trimmed due to the manufacturing identifications.

##### Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

Re-decorate the door as necessary always following the paint manufacturer's instructions.

